

# Screened Gypsum

## STATEMENT OF HAZARDOUS NATURE

This product contains low levels of crystalline silica, a substance that has been classified by the IARC as "Group 1 - Carcinogenic To Humans When Inhaled From Occupational Sources".

**AVOID EXPOSURE TO EXCESSIVE DUST AND  
ALWAYS WEAR AN APPROVED MASK IF MILLING  
OR GRINDING.**

## COMPANY DETAILS:

**Company** Winstone Wallboards Ltd  
**Address:** P.O. Box 12 256  
Penrose  
Auckland  
NEW ZEALAND  
**Telephone:** +64 (9) 633 0100  
**Facsimile:** +64 (9) 633 0101  
**Emergency Telephone Number:** +64 (3) 474 7000

---

## IDENTIFICATION

---

### PRODUCT INFORMATION:

**Product Name:** Screened Gypsum  
**Synonyms:** Land Plaster, Alabaster, Selenite, Gypsum Rock  
**Manufacturers Product Code:** GSB040, GSB010, GSB100  
**Product Group:** Gypsum Rock.  
**Chemical Family:** Calcium Sulphate  
**Product Use:** Agricultural Gypsum  
**Dangerous Goods Class** Not allocated

### INGREDIENTS

Material	Content %	TLV mg m <sup>-3</sup>	CAS No.
Calcium Sulphate Dihydrate	100	10	10101-41-4
Crystalline Silica(Total From Above)	<2.0	0.1	14808-60-7

NE Not Established      NA Not Available

## Screened Gypsum

### PHYSICAL DATA

<b>Appearance &amp; Odour:</b>	Off White to Grey Powder. Low Odour.
<b>Melting Point:</b>	1450 °C – decomposes.
<b>Solubility In Water:</b>	2.41 g/L @ 20°C
<b>Specific Gravity (Water = 1):</b>	2.3 – 2.6
<b>pH:</b>	7.5 – 8.5

---

### HEALTH HAZARD DATA

---

#### HEALTH EFFECTS:

<b>Acute:</b>	<b>Swallowed:</b>	Calcium sulfate dihydrate is non-toxic, however, ingestion of a sufficient quantity could lead to mechanical obstruction of the gut, especially the pyloric region. Call physician.
	<b>Eye:</b>	Direct contact can cause mechanical irritation of eyes. If burning, redness, itching, pain or other symptoms persist or develop, consult doctor.
	<b>Skin:</b>	Direct, prolonged or repeated contact with the skin may cause irritation. Rubbing of this product against the skin can result in abrasions. Rinse with water until free of material to avoid abrasions, then wash skin thoroughly with mild soap and water. May dry skin. If irritation persists, consult doctor.
	<b>Inhaled:</b>	Inhalation of dusts from this product may irritate the nose, throat, lungs, and upper respiratory tract. Persons subjected to large amounts of this dust will be forced to leave area because of nuisance conditions such as coughing, sneezing and nasal irritation from dust. Laboured breathing may occur after excessive inhalation. If respiratory symptoms persist, consult doctor.
<b>Chronic:</b>	<b>Swallowed:</b>	None known.
	<b>Eye:</b>	None known.
	<b>Skin:</b>	The powder will dry the skin. Prolonged exposure may cause cracking of the skin.
	<b>Inhaled:</b>	Respirable dust may cause lung disease or cancer. Prolonged breathing of excessive dust may adversely affect lung function.

## Screened Gypsum

### EMERGENCY & FIRST AID PROCEDURES:

<b>Treatment:</b>	<b>Swallowed:</b>	No harmful effects expected. No specific recommendation. If gastric disturbance occurs, call doctor.
	<b>Eye:</b>	Immediately flush thoroughly with water for 15 minutes. If irritation persists, see doctor.
	<b>Skin:</b>	Wash with mild soap and water. A commercially available hand lotion may be used to treat dry skin areas.
	<b>Inhaled:</b>	Remove to fresh air. Leave the area of dust exposure and remain away until coughing and other symptoms subside. Other measures are usually not necessary, however if conditions warrant, contact doctor.
<b>Target Organs:</b>		Eyes, skin, and respiratory system.
<b>Medical Conditions Which May Be Aggravated:</b>		Pre-existing upper respiratory and lung diseases such as, but not limited to, bronchitis, emphysema and asthma.
<b>Primary Route Of Entry:</b>		Inhalation; Eye and/or Skin contact.
<b>Facilities:</b>		Eye wash bottles/tap.

---

### PRECAUTIONS FOR USE

---

### REACTIVITY DATA:

<b>Stability:</b>	Stable under normal conditions
<b>Hazardous Polymerisation:</b>	Will not occur
<b>Conditions To Avoid:</b>	Reduces violently when mixed with Aluminium Powder or Red Phosphorus at high temperature (>800 °C)
<b>Hazardous Decomposition Products:</b>	Above 1450 °C – CaO and SO <sub>2</sub> .

### PERSONAL PROTECTION INFORMATION:

<b>Respiratory Protection:</b>	During general handling a two-strap type dust mask is suitable. During milling or grinding of material use of an approved cartridge type mask is recommended.
<b>Ventilation:</b>	General or local ventilation during milling or grinding of material.
<b>Protective Equipment:</b>	Safety Glasses.

## Screened Gypsum

---

### SAFE HANDLING PROCEDURES

---

#### SPILLS & DISPOSAL

<b>Spill/Leak Procedures:</b>	Product should be swept or vacuumed up, keeping dust generation to a minimum.
<b>Waste Disposal Method:</b>	To standard landfill.

#### FIRE & EXPLOSION DATA

<b>Flash Point (Method Used):</b>	Non Combustible.
<b>Extinguishing Media:</b>	Use extinguishing media appropriate for surrounding fire.
<b>Special Fire Fighting Procedures:</b>	None
<b>Unusual Fire &amp; Explosion Hazard:</b>	None
<b>Special Fire Fighting Protective Equipment::</b>	None

#### STORAGE & TRANSPORT:

<b>Precautions In Storage:</b>	Packaged product should be kept dry and away from moisture. It is hygroscopic and tends to cake in moist environments.
<b>Precautions In Transport:</b>	Minimise exposures in accordance with good hygiene practice. During handling wear the appropriate respiratory, eye and skin protection if warranted per environmental conditions.

---

### OTHER INFORMATION

---

**KEEP OUT OF REACH OF CHILDREN**